



700
TVL
HI RES

Enhanced
High-resolution Cameras

SOLARVAC-SOLAMAGIC
3/37 Howe St Osborne Park WA
Ph: 9244 4611 Fax: 9446 7339
www.(&info@)solarvac.com.au

4 Channel Advanced CCTV kit

VIEW REMOTELY
on your mobile device

Windows OS and Symbian software supplied. For iPhone search the App Store for "KMEye"



1 Terabyte
Hard Drive



4 Channel
DVR



4 IR Cameras
included



Mouse
Control



IR Remote
Control



Inc Cables &
Accessories



CE FC N55

DVR Features & Benefits

- Networkable DVR for Remote Access via Web
- Surveillance via Web Browser and Mobile Phone
- Plug & Play including Cables for Fast Installation
- H.264 High Quality Video Compression
- Supports 1TB SATA Hard Drive for extra storage
- Host USB for easy Back-Up
- Dual Video Outputs - Composite & VGA
- Motion Detection / Continuous / Schedule Record
- Time/Date/Event Quick Search for Fast Searching
- IR Remote Control included
- Mouse included

Camera Features & Benefits

- 700TVL High Resolution for capturing fine detail
- Weatherproof IR Ball Camera for indoor/outdoor use
- Built-in 36 x IR LEDs for Day and Night use
- 30m IR Range for effective night-time illumination
- Smart-IR to avoid over-brightness on near objects
- Dual Glass to avoid IR Reflection
- Tough Vandal Proof Metal Housing
- External Zoom/Focus for easy adjustment

Kit Contents

- 1 x 4ch Networkable DVR
- 4 x High-res Colour Dome Cameras with IR
- 1 x 1000GB (1TB) Hard Drive
- 4 x 15m Video/Power Cables
- 1 x IR Remote Control
- 1 x Mouse
- 1 x Power Supply
- Network and audio patch cables.

104-509 CCTV KIT

DVR SPECIFICATIONS

Description	4CH H.264 DVR with VGA&Network
Video Input	4ch video input (1.0Vp-p 75ohm BNC TYPE)
Video Output	2ch Output (Main BNC*1, VGA*1)
Screen Split	Full Screen, 4 Screen Split
Display Resolution	PAL: 720(H) X 576(V)
Display Speed	PAL:100 fps(4X25fps)
Playback Resolution / Speed	PAL: 720(H) X 576(V) / D1, 25fps(4x6.25fps) PAL: 720(H) X 288(V) / HD1, 50fps (4x12.5fps) PAL: 360(H) X 288(V) / CIF, 100fps (4x25fps)
Storage	SATA HDD, Up to 1000GB
Compression	H.264
Record Mode	Continue/ Motion Detect/ Schedule / Manual
Search Mode	Time/ Date/ Event
Back-up	HOST USB, Network
VGA Output	Support 800*600, 1024*768, 1280*1024
Network Protocol	TCP/IP, DHCP, DNS, DDNS, PPPoE
Network Functionality	Supports IE Browser, Real-Time Network Monitoring, Network DVR Parameter Setting
PTZ Control	RS-485 Interface Built-in, Support Pelco-D, Pelco-P Protocol
Dimensions	274mm X 215mm X 45mm
Mouse Support	Yes
IR Remote Controller	Yes
Weight	1.09 kg
System	PAL
Power Supply	ADAPTER(12V DC 3A)

CAMERA SPECIFICATIONS

Image Sensor	1/3" Sony Super-HAD II High Image CCD
Total Number of Pixels	PAL: 976(H) X 582(V)
Resolution	700 TV Lines
Lens	2.8 ~ 12mm Varifocal Lens
BNC Video Output	1.0 Vp-p. 75 ohm
Gamma	0.45
S/N Ratio	> 48dB
Min. Illumination	0.1LUX/F1.4 (0 LUX IR On)
Sync. Mode	Internal Sync.
Scanning System	2:1 Interlace
Shutter Control	PAL:1/50~1/100,000sec
Shutter Speed	Auto
Back Light Compensation	Auto
Gain Control	Auto
White Balance	Auto
Day/Night	Built-in 36pcs IR LED
IR Distance	30 Metres
Power	12V DC
Dimension	119mm(Ø) X 100mm(H)
Weight	610g



Innovative Electronic Solutions

www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au